

ValueJet

ValueJet VJ-1624



High quality printer for durable graphics

The Mutoh ValueJet 1624 printer (1625 mm – 64") incorporates the very latest piezo drop-on-demand head technology and new generation electronics. Targeted at sign and display applications, the printer addresses the needs of businesses focusing on both high speed production and top quality print work.

The VJ-1624 is ideal for established sign makers who need extra versatility and for larger operations that want to extend their capacity and flexibility. A ValueJet 1624 will deliver best-in-class speed and superior print quality, without compromise.

Product Highlights

- Powerful printer, featuring new head technology
- Increased print speeds & improved print quality
- Proven technology plus a new set of innovative comfort features
- Impeccable print quality every time with Mutoh Intelligent Interweaving print technology (i²)
- Print speeds up to 29.1 m²/h

Application Possibilities

The VJ-1624 is suited for the production of a wide variety of outdoor and indoor prints : long-term outdoor posters, billboards, building announcements, signs and banners, backlit signage, POS displays, vehicle graphics, fine art reproduction, posters, etc..



MUTOH



ValueJet VJ-1624



64" Sign & Display Printer

SPECIFICATIONS

Technical Key Specifications

Print Technology	Drop-on-demand Micro Piezo Inkjet Technology
Print Head	1
Nozzle Configuration	180 nozzles x 8 lines
Drop Mass Range (pl)	3.5 to 35.2
Head Heights (mm)	Low : 1.5 / High : 2.5

Media Specifications

Max. Media Width	1625 mm (63,97")
Max. Print Width	1615 mm (63,58")
Max. Media Thickness	0.3 / 1.3 mm *

* : Max. media thickness is specified per head height

Media Measurements *	Ø 150 mm / 2" & 3" / 30 kg
----------------------	----------------------------

* : Standard non-motorised roll-off system

Media Drying System	Individually controlled pre-heater, fixer & dryer (30 - 50 °C)
---------------------	--

Ink Specifications

Ink Types	Eco Ultra / UMS
Ink Volume	220 ml & 440 ml & 1000 ml* / 440 ml & 1000 ml
* : 1000 ml bag requires optional adapter	
Ink Colours	CMYK
Ink Consumption *	8 ml / m ²

* : Average ink consumption graphics at @ 720 dpi - coverage of 67 %

UV durability - without lamination	3 years outdoor *
------------------------------------	-------------------

* : For heavy duty applications where mechanical stress is involved, lamination is required. Stabilisation is required prior to lamination.

Performance

High Quality (720 x 1080)	5.0 m ² /h
Quality (720 x 720)	7.5 m ² /h
Quality Production (720 x 1080)	10 m ² /h
Production (720 x 720)	14.5 m ² /h
Speed Production (720 x 720)	20.5 m ² /h
Billboard (360 x 720)	29.1 m ² /h

Power Consumption

During Printing	< 600 W
In Stand-by	45 W
Warming Up	≤ 1100 W (main) & ≤ 1200 W (heat)
Power Supply	AC 100-120 V / AC 200-240 - 60/50 Hz

Recommended Working Environment

Temperature	22 °C - 30 °C with Δt: max. 2 °C/h
Humidity	40 % - 60 % (no condensation) with ΔRH: max. 5% RH/h

Machine Measurements

Width x Depth x Height	2698 x 885 x 1261 mm
Weight	160 kg

Distributed by:

