# ValueUet

## ValueJet VJ-1324



## High quality printer for durable graphics

The cost-effective professional ValueJet 1324 (1371 mm - 53.97") is perfectly suited for small to mid-range sign makers and print providers.

Flexible, reliable and able to deliver excellent print quality for volume production runs as well as short print runs, this printer will prove to be a reliable workhorse for all high-quality indoor and outdoor banners, vehicle graphics, backlit displays and much more. A perfect match for businesses with medium and higher print volumes.

### Product Highlights

- Powerful printer, featuring new head technology
- Increased print speeds & improved print quality
- Proven technology plus a new set of innovative comfort features
- Impeccable print quality every time with Mutoh Intelligent Interweaving print technology (i<sup>2</sup>)
- Print speeds up to 27.9 m<sup>2</sup>/h

### **Application Possibilities**

The VJ-1324 is suited for the production of a wide variety of outdoor and indoor prints: long-term outdoor posters, billboards, building announcements, signs and banners, backlit signage, POS displays, vehicle graphics, fine art reproduction, posters, etc..















# ValueUet

## ValueJet VJ-1324



## 54" Sign & Display Printer

#### **Technical Key Specifications**

, ,	
Print Technology	Drop-on-demand Micro Piezo Inkjet Technology
Print Head	1
Nozzle Configuration	180 nozzles x 8 lines
Drop Mass Range (pl)	3.5 to 35.2
Head Heights (mm)	Low: 1.2 / High: 2.0

#### Media Specifications

Max. Media Width	1371 mm (53,97")	
Max. Print Width	1361 mm (53,58")	
Max. Media Thickness	0.3 / 1.3 mm *	
*: Max. media thickness is specified per head height		
Media Measurements *	Ø 150 mm / 2" & 3" / 19 kg	

<sup>\*:</sup> Standard non-motorised roll-off system

Media Drying System	Individually controlled pre-heater,
	fixer & dryer (30 - 50 °C)

#### Ink Specifications

Ink Type	Eco Ultra / UMS	
Ink Volume	220 ml cassette & 1000 ml bag */ 1000 ml	
*: 1000 ml bag requires optional adapter		
Ink Colours	CMYK	
Ink Consumption *	8 ml / m <sup>2</sup>	
*: Average ink consumption at @720 dpi - coverage of 67 %		

UV durability – without lamination 3 years outdoor \*

\*: For heavy duty applications where mechanical stress is involved, lamination is required.

Stabilisation is required prior to lamination.

## **SPECIFICATIONS**

#### Performance

High Quality (720 x 1080)	3.9 m²/h
Quality (720 x 720)	5.9 m <sup>2</sup> /h
Quality Production (720 x 1080)	7.9 m <sup>2</sup> /h
Production (720 x 720)	11.8 m <sup>2</sup> /h
Speed Production (720 x 720)	16.4 m <sup>2</sup> /h
Billboard (360 x 720)	27.9 m <sup>2</sup> /h

#### Power Consumption

During Printing	< 500 W
In Stand-by	45 W
Warming Up	≤ 1550 W
Power Supply	AC 100-120 V /
	AC 200-240 - 60/50 Hz

#### Recommended Working Environment

Temperature	22 °C - 30 °C with Δt: max. 2 °C/h
Humidity	40 % - 60 % (no condensation)
	with ∆RH: max. 5% RH/h

#### Machine Measurements

Width x Depth x Height	1916 x 685 x 1218 mm
Weight	82.3 kg

#### Distributed by:

